



TECHNICAL SPECIFICATIONS ASR665

DESCRIPTION

A biamplified 3-way full range system (passive mid/high crossover) in a rectangular enclosure. Includes a 15-in woofer (vented), a horn-loaded 10-in MF cone and a 1.4-in exit/44mm voice coil HF compression driver on a 60 x 45 constant directivity horn.

APPLICATION

The ASR665 is engineered for use in permanent installations. The low profile 22.5-in enclosure height lets it be used in applications where loudspeaker mounting space is limited. Includes comprehensive 3/8"-16 mounting/suspension points. Six year warranty.

Applications include:

- Stadiums
- Arenas
- Dance Clubs
- Theaters
- Performing Arts Centers
- Houses of Worship

DESCRIPTIVE DATA

Part Number	999675
Product Group	I
System Configuration	3-way, Full Range
Powering Configuration(s)	Biamplified (passive MF/HF crossover)
LF Subsystem & Loading	1x 15-in, Vented
MF Subsystem & Loading	1x 10-in, Horn-Loaded
HF Subsystem & Loading	1x 1.4-in exit/44mm voice coil Compression Driver on Constant Directivity Horn
Recommended High-Pass Frequency (24 dB/Octave)	40 Hz
System Crossover	320 Hz
Cabinet Type (shape)	Rectangular
Enclosure Materials	Baltic Birch Plywood
Finish	Black Polyurethane
Connectors	2 x 2-Terminal Barrier Strip
Suspension Hardware	(12) 3/8"-16 Threaded Mounting/ Suspension Points (3 each Top and Bottom, 2 on Sides and Back)
Grill	Powder Coated Perforated Steel
Options	104001 3/8"-16 Eyebolt (FC300B)



NOMINAL DATA


Frequency Response (1 Watt @ 1m)		
±3 dB	47 Hz to 17 kHz	
-10 dB	40 Hz	
Axial Sensitivity (dB SPL, 1 Watt @ 1m)		
Passive MF/HF	105	
LF	97	
Impedance (Ohms)		
Passive MF/HF	8	
LF	8	
Power Handling, AES Standard (Watts)		
Passive MF/HF	360	
LF	600	
Calculated Maximum Output (dB SPL @ 1m)		
Passive MF/HF Peak	136.6	
LF Peak	130.8	
Passive MF/HF Long term	130.6	
LF Long Term	124.8	
Nominal Coverage Angle/-6 dB points (degrees)		
Horizontal	60	
Vertical	45	
Dimensions		
	inches	millimeters
Height	22.50	572
Width	41.50	1054
Depth	19.75	502
Weights		
	pounds	kilograms
Net Weight	152	69.2
Shipping Weight	170	77.4





TECHNICAL SPECIFICATIONS ASR665

DIMENSIONAL DRAWING



ARCHITECTURAL SPECIFICATIONS

The biamplified 3-way full range loudspeaker systems shall incorporate a 15-in LF transducer, a 10-in MF cone and a 1.4-in exit/44mm voice coil HF compression driver.

The LF driver shall be mounted in a vented enclosure tuned for optimum low frequency response. The MF driver shall be loaded into a midrange horn constructed of 3mm birch plywood backed with high density polyurethane foam. The HF driver shall be loaded on a constant directivity horn with a nominal coverage pattern of 60° (h) x 45° (v). An internal passive filter network shall provide fourth order acoustical crossover and system equalization between the MF and HF subsystems.

System frequency response shall vary no more than ± 3 dB from 47 Hz to 17 kHz measured on axis. The mid/high section shall produce a Sound Pressure Level (SPL) of 105 dB SPL on axis at 1 meter with a power input of 1 Watt, and shall be capable of producing a peak output of 136.6 dB SPL on axis at 1 meter. The low frequency section shall produce a Sound Pressure Level (SPL) of 97 dB SPL on axis at 1 meter with a power input of 1 Watt, and shall be capable of producing a peak output of 130.8 dB SPL on axis at 1 meter. The mid/high section shall handle 360 Watts of amplifier power (AES Standard) and shall have a nominal impedance of 8 Ohms. The low frequency section shall handle 600 Watts of amplifier power (AES Standard) and shall have a nominal impedance of 8 Ohms.

The loudspeaker enclosure shall be rectangular in shape. It shall be constructed of 15mm thickness void-free cross-grain-laminated Baltic birch plywood and shall employ extensive internal bracing. It shall be finished in black polyurethane. Input connectors shall be 4-terminal barrier strip. Twelve (12) 3/8"-16 threaded mounting/suspension points (3 each top and bottom, 2 on each side and back) shall be provided. The front of the loudspeaker shall be covered with a powder coated perforated steel grill.

The biamplified 3-way full range loudspeaker shall be the EAW model ASR665.

SERVICE ITEMS

LF: Complete Cone Driver	EAW Part No. 804081
MF: Complete Cone Driver	EAW Part No. 804021
HF: Complete Compression Driver/Tweeter	EAW Part No. 803039
LF: Recone Assembly	EAW Part No. 46059
MF: Recone Assembly	EAW Part No. 460010
HF: Diaphragm Assembly	EAW Part No. 806019
Filter/Crossover Network: Complete Assemble	EAW Part No. 255341