

OEC1366x Processor Settings

January 2, 2006



OEC1366x tri-amp

OEC1366x bi-amp

OUTPUT	Name
GAIN	(dB)
DELAY	(ms)
POLARITY	
HPF	Freq (Hz)
	Slope (dB)
	Shape
LPF	Freq (Hz)
	Slope (dB)
	Shape
PEQ1	Freq (Hz)
	Level (dB)
	Type
	Q
	(Bandwidth)
PEQ2	Freq (Hz)
	Level (dB)
	Type
	Q
	(Bandwidth)
PEQ3	Freq (Hz)
	Level (dB)
	Type
	Q
	(Bandwidth)
PEQ4	Freq (Hz)
	Level (dB)
	Type
	Q
	(Bandwidth)
PEQ5	Freq (Hz)
	Level (dB)
	Type
	Q
	(Bandwidth)

LF	MF	HF
11.0	0.0	4.0
0.12	0.00	0.35
Positive	Positive	Positive
35	274	1496
24	24	24
Linkwitz-Riley	Linkwitz-Riley	Butterworth
251	1496	21983
24	24	12
Linkwitz-Riley	Butterworth	Bessel
59	668	1995
6.0	-1.5	-5.0
Parametric	Parametric	Parametric
2.00	2.00	1.68
0.50	0.50	0.60
211	2113	5956
-4.0	-13.0	3.0
Parametric	Parametric	Parametric
2.00	8.90	1.00
0.50	0.17	1.00
		11885
		3.0
		Parametric
		2.00
		0.50

LF	MF/HF
11.0	0.0
0.00	0.00
Positive	Positive
35	274
24	24
Linkwitz-Riley	Linkwitz-Riley
258	21983
24	12
Linkwitz-Riley	Bessel
59	728
6.0	-3.0
Parametric	Parametric
2.00	2.00
0.50	0.50
211	1188
-4.0	1.0
Parametric	Parametric
2.00	3.00
0.50	0.33
	5956
	5.0
	1
	2.00
	0.50
	11885
	3.0
	Parametric
	2.00
	0.50

Output gains assume all amplifiers have the same voltage gain